





Pulse Cleaning Fiber Laser

YLPN-Clean-300-2/500/10-F

Pulsed cleaning fiber laser is a high efficiency, high reliability, high-performance pulsed fiber laser series, easy to operate, can be directly integrated into the user equipment, small size, light weight, space saving.

Advantages


- New thermal design,more reliable,longer working time
- MOPA construction, pulse width 2-500ns adjustable, maximum single pulse energy 2mJ
- PRF and PW can be controlled independently
- AC or DC input optional

The professional performance laser series of GW is aimed at customers who have the pursuit of product performance indicators, the replacement of imported products or the product functionality requirements. Product design to the first-line brand, with better product performance indicators, perfect functions, design redundancy is greater, to provide customers with more value-added space.

Applications

Widely used in new energy battery welding, cleaning and cutting fields, the specific applications are pole cutting, blue film cleaning, pole cleaning, battery parts before welding cleaning (including cover plate, liquid injection hole, pole), pole laser drilling, laser marking and precision spot welding.

- Multi-power optional, compact structure
- PRF and PW can be controlled independently
- Perfect laser characteristics and good pulse shape control
- Easy to operate and maintenance-free










www.gwlaser.tech LASER AS A Tool


Pulse Cleaning Fiber Laser

YLPN-Clean-300-2/500/10-F

Product specification parameter	YLPN-Clean-300-2/500/10-F
Output Power (watt)	300
Operating Mode	Pulse
Output Power Range (%)	1-100
Output Laser Wavelength (nm)	1070±10
Beam Quality	M²≤1.7
Pulse Width (ns)	QCS
Power Stability	30um
Cooling Method	Forced air cooling
Ambient Temperature Range (°C)	0-40
Input Voltage	48VDC/220VAC 50Hz
Dimension (mm)	420 x 180 x 330 (L×W×H)
Weight (kg)	< 25







Legal Notice: All product information is believed to be accurate and subject to change without notice.

Legal statement:

GW smart fiber laser products are designed in strict accordance with safety regulations. All production is in accordance with international standards and regulations currently in force in the country. Each GW laser has a warning sign as shown in the figure.

MAX. AVERAGE OUTPUT POWER: 12 kW MAX. PEAK OUTPUT POWER: 20 kW PULSE DURATION: 0.2-2 ms PULSE REPETTION RATE: 50 Hz-10 kHz WAVELENGTH RANGE: 900-1200 nm DANGER - INVISIBLE LASER RADIATION AVOID EYE OR SKIN EXPOSURE TO DIRECT OR SCATTERED RADIATION CLASS 4 LASER PRODUCT IEC 60825-1:2014



